











The HMi 1302-Z2







Fully Certified



Crisp & Bright Display



Super Fast Processor



Precision Engineered

With easy-to-use features, touchscreen controls and a super-bright, 1000 Nit glove friendly, multi-touch 19" sunlight viewable display. Lightweight, rugged, IP66 and field maintainable.



The HMi 1302-Z2

















Certification

Certified to ATEX, IECEx, AEx (NEC505) Section 18 CSA 22,2 EAC.



Light & Slim

Weighing in at just 12.5kg / 27.6lbs the 1302-Z2 is just 95mm / 3.74 inches thin



Crisp & Bright Display

A high-bright 1000 nit display in the lightest of enclosures.



Super Fast Processor

The intel core i7 processor works 100% from -40°C to +60°C - no throttling back here.



Precision Engineered

Machined from a single piece of aluminium, this is precision engineering at its finest.

United Kingdom

HMi Elements Ltd Unit A & B, Windmill Industrial Estate, Showfield Lane, Malton, UK, YO17 6BT +44 (0) 1653 699 908

United States

HMi Elements Inc 10900 Brittmoore Park Drive, Suite I, Houston, TX 77041, USA T +1 (0) 281 674-7815

Design and specifications subject to change without notice Errors and omission excepted

PRODUCT TYPE PC Workstation MODEL NO 1302-72 TYPICAL EX CODE ATEX: II 3(3)GD, Ex nA [ic Gc] IIC T4 Gc, Ex tc IIIC T135°C Dc IECEx: Ex nA [ic Gc] IIC t4 Gc, Ex tc IIIC T135°C Dc CSA: Class I, Div 2, Groups A, B, C, D; Temperature Code T4 Class II Div 1, Groups E, F, G;, Class III, Type 4X Canada: Ex nA [ic] IIC T4, Ex tb IIIC T135°C Db, USA: AEx nA [ic] IIC T4, Zone 21 AEx tb IIIC T135°C IP66 Projected Capacitive Technology (PCT) - Multi Touch, Glove Friendly DISPLAY SIZE **DISPLAY TYPE** Sunlight Viewable Glove-Friendly 1000 nit Capacitive LCD Touchscreen SXGA; 1280 x 1024, wide viewing angle, 24 bit colour RESOLUTION PROCESSOR OPTIONS Dual Core Atom 1.86GHz Intel Core i7, 6th Gen Skylake 6600U OPERATING SYSTEM Windows 10 Enterprise LTSB & LTSC, Windows 7 Professional 64 Bit 64GB SSD (standard) SSD OPTIONS 64GB SSD (standard) also available + second 64GB SSD (optional) 128GB or 256GB SSD + second drive 64, 128, 256GB SSD (optional) RAM 4GB 8GB + Option to upgrade to 16Gb or 32Gb **COMM OPTIONS** 2 wired Ethernet port triple speed (10/100/1000Mbits/s) or 1 wired Ethernet port triple speed (10/100/1000Mbits/s) with Fiber Optic Ethernet, Wi-Fi (802.11 b/g/n), 2 x Gigabit Ethernet Optional 1310nM Fibre KEYBOARD / MOUSE / Intrinsically Safe PS/2 Interface TOUCHSCREEN 2 x USB ports SERIAL COMMUNICATIONS One RS232 and one RS422/RS485 INGRESS PROTECTION IP66 / NEMA4 and NEMA 4X **OPERATING TEMPERATURE** -40°C to +60°C STORAGE TEMP -40°C to +85°C (-40°F to +185°F) WEIGHT 12.5kg / 27.6lbs MAX DIMENSIONS W 476mm (18.74") x H 427mm (16.81") x D 95mm (3,74") MOUNTING OPTIONS VESA, Yoke, Panel SHOCK & VIBRATION Shock: In accordance with BS EN60068-2-27:2009 Vibration: In accordance with BS. EN60068-2-6:2008

