



















Fully Certified



Crisp & Bright Display



Super Fast Processor



Precision Engineered

Show-stopping design meets rugged toughness, in this revolutionary 19" machine built to survive the challenges of any Zone 1 environment.

Crafted from a single piece of aluminum, the 1301 is lighter and slimmer than other Zone 1 HMI's, IP66 and field maintainable too.

hmielements.com

The HMi 1301-Z1











Certification

Certified to ATEX, IECEx, AEx (NEC505) Section 18 CSA 22,2.



Light & Slim

Weighing in at just 25.2Kg / 55.5bs, the 1301-Z1 is just 95mm/ 3.74inches thin.



Crisp & Bright Display

A high-bright 1000 nit display.



Super Fast Processor

The intel core i7 processor works 100% from -40°C to +60°C - no throttling back here.



Precision Engineered

Machined from a single piece of aluminium, this is precision engineering at its finest.

United Kingdom

HMi Elements Ltd Unit A & B, Windmill Industrial Estate, Showfield Lane, Malton, UK, YO17 6BT +44 (0) 1653 699 908

United States

HMi Elements Inc 10900 Brittmoore Park Drive, Suite I, Houston, TX 77041, USA T +1 (0) 281 674-7815

hmielements.com



| [] ** = *T | |
|-----------------------|--|
| TYPICAL EX CODE | II2 GD Ex eb db mb op is [ib] IIC T4 Gb Ex tb IIIC T90°C Db |
| | Class 1, Zone 1, AEx |
| | eb db mb op is [ib] IIC T4 Gb |
| | Zone 21 Ex tb IIIC T90°C Db IP66 |
| POWER REQUIREMENTS | Built in 90 - 250 VAC Power Supply |
| OPERATING TEMPERATURE | -40°C to +60°C (+55°C with media converter fitted) |
| STORAGE TEMPERATURE | -40°C to +85°C. |
| HUMIDITY | 10 to 90 % non-condensing, operating. 0 to 100 % non-operating. |
| WEIGHT | 25.2kg / 55.5lbs (Excluding connectors, cables and accessories) |
| SIZE | 476(W) x 427(H) x 95(D)mm / 18.74" x 16.81" x 3.74" |
| MATERIAL | Enclosure is Aluminium Alloy 7075 Hard Anodised Natural Finish. External Fixings and Accessories SS316 or similar |
| INGRESS PROTECTION | IP66/NEMA4X. |
| INTERFACES | Ethernet, USB, RS232, RS485, IS Horn |
| PROCESSOR/MEMORY | Intel iCore 6th/7th generation Memory Options DDR4 - 8, 16 or 32 Gbytes DDR4 DRAM |
| DISPLAY | 19" SXGA,1280x1024, wide viewing angle, 24 bit colour. Sunlight readable high brightness panel, IR filtering and anti-glare coating. |
| TOUCHSCREEN | Projected Capacitive. |
| DIAGNOSTICS | LED diagnostic indicators |
| OPTIONS | Wi-Fi connectivity IS Bluetooth connectivity Fibre optic connectivity (op IS) Remote interrogation of on-board diagnostics Built in camera |

Design and specifications subject to change without notice Errors and omission excepted

